

AIR-COOLED SPLIT SYSTEM SSW SERIES WM-1500SSW



## **Key Features**

- Stable temperature between 50~65 °F for a properly insulated room in a normal environment
- Maintain humidity of 50~75% RH even when the environment becomes dry or humid
- The condensing units can be placed up to 75 ft away from the wine room, which will allow for extremely quiet operation
- These units require professional installation by a licensed refrigeration technician
- Perfect for storing cigars, chocolate, salami, and fine leather and furs (additional cost and customization required)

## **Specifications**

Cellar Size:	150 cu ft
Btu/h and CFM:	1500 Btu/h and 105 CFM
Decibel Rating:	53 dBA
Dimensions:	Evaporator: 16"W x 5-1/2"D x 36"H Condenser: 18"W x 14"D x 12"H
Electrical:	Evaporator: 115V/60Hz/1A Condenser: 115V/60Hz/4A
Weight:	Evaporator: 25 lbs Condenser: 30 lbs
Refrigerant:	R134a
Thermostat:	Advanced Digital Control Display

## Wine-Mate 1500SSW Split Wall-Recessed Wine Cooling

## **Features**

System

Wine-Mate wall split cooling systems WM-1500~4500SSW are designed and used to provide a cold temperature between 50~65 °F for a properly insulated wine cellar. The wine cellar will maintain humidity range within 50~75% RH. These temperature and humidity ranges like in natural caves are optimized for long term storage of wine. SSW units consist of a condensing unit and an evaporator unit; they are connected by a liquid line and an insulated suction line. SSW condensing units can be located away from the wine cellars 75 ft so that noise and compressor vibration are isolated. SSW evaporator units can be installed inside a wine rack or between two wall studs, making them an ideal choice for wine cabinets or small wine rooms.

732 South Racetrack Road, Henderson, NV 89015 U.S.A. 1.800.777.8466 | Fax 310.886.3310 | info@vinotemp.com | www.WINEMATE.com